

Dr. Dietrich Müller GmbH, Zeppelinring 18, D-26197 Ahlhorn

Standard products

Glass sleeve SP 62165

Composition: SP 62165 is a raw glass sleeve that means this glass sleeve is uncoated.

Properties: SP 62165 has good thermal and dielectric properties and good flexibility.

Applications: SP 62165 is used as insulation for wires and as mechanical protection for electrical machines, electrical applications, and electrical instruments up to insulation class F.

Delivery forms: SP 62165 is delivered in natural colour on rolls or as cuts.

Storage requirements: SP 62165 should be stored at room temperature in its original packaging.

Status October 2014

Zeppelinring 18 | D-26197 Ahlhorn | Tel.: +49 (0) 4435 97 10 10 | Fax: +49 (0) 4435 97 10 11
info@mueller-ahlhorn.com | www.mueller-ahlhorn.com | Sitz der Gesellschaft: Ahlhorn
Geschäftsführer: Heinz-Jürgen Siebert | AG Oldenburg: HRB 209026 | Ust. ID-Nr.: DE 295969093
St.-Nr.: 68/207/07677 | Zertifiziert nach DIN EN ISO 9001:2008 | UL anerkannter Repacker E341377

Dr. Dietrich Müller GmbH

- Elektroisierstoffe
- Dichtungen
- Wärmeleitprodukte
- Technische Folien

Dr. Dietrich Müller GmbH, Zeppelinring 18, D-26197 Ahlhorn

Glass sleeve SP 62165

Property	Unit	Value
Insulation class	-	F
Dielectric strength	kV	-
Continuous working temperature	-	-25 °C/ +500°C
Thickness (Bore size 4.0 – 6.0 mm)	mm	0.25
Thickness (Bore size 7.0 – 25.0 mm)	mm	0.40

Please note:

The information in this data sheet are based on our current knowledge and experience. They do not disengage the fabricator and user from own tests and inspections because of the plenty of possible effects. There is no judicial binding assurance of certain properties or of the qualification for a concrete application in our declaration. We recommend consulting us in individual cases. The acceptor of our products has to observe possible industrial property rights as well as present laws by himself.

Status October 2014

Zeppelinring 18 | D-26197 Ahlhorn | Tel.: +49 (0) 4435 97 10 10 | Fax: +49 (0) 4435 97 10 11
info@mueller-ahlhorn.com | www.mueller-ahlhorn.com | Sitz der Gesellschaft: Ahlhorn
Geschäftsführer: Heinz-Jürgen Siebert | AG Oldenburg: HRB 209026 | Ust. ID-Nr.: DE 295969093
St.-Nr.: 68/207/07677 | Zertifiziert nach DIN EN ISO 9001:2008 | UL anerkannter Repacker E341377

Dr. Dietrich Müller GmbH

- Elektroisierstoffe
- Dichtungen
- Wärmeleitprodukte
- Technische Folien