

Tapes

3M™ 950

Material: 3M™ 950 is a transfer tape with a modified acrylic adhesive.

Properties: 3M™ 950 offers high instant adhesion and good shear strength and adhesion strength. It can be used on coarse and uneven surfaces. The liner of 3M™ can be easily removed and has good processing and die-cut characteristics.

Applications: 3M™ 950 is used for foam materials, films, metal- and plastic signs, ledges, pictures, promotional materials, etc. to make them self-adhesive.

Colour: transparent

Property	Unit	Value
Adhesive		Modified acrylic
Base material		-
Colour		Transparent
Thickness	mm	0,13
Liner		Paper
Peelstrength on steel	N/100 mm	80
Temperature resistance	°C	80
Long-term		120
Short-term		
Solvent resistance		Good
UV-resistance		Good
Softening agent resistance		Good

Dr. Dietrich Müller GmbH

3M™ 950

Please note:

The information in this data sheet is based on our current knowledge and experience. They do not disengage the fabricator and the user from own tests and inspections because of the plenty of possible effects. There is no judicial binding assurance of certain properties or of the qualification for a concrete application in our declaration. We recommend consulting us in individual cases. The acceptor of our products has to observe possible industrial property rights as well as present laws by himself.

Dr. Dietrich Müller GmbH