

# Laminates

## Rigidiso® RI 40220

**Structure:** Rigidiso® RI 40220 is an Epoxy Glass fibre netting consisting of high strength E-glass yarn without wax, which is woven by special technology. It has the advantage of proportional spacing and fixing meshes. After coating with imported epoxy resin, the product provides good hardness and toughness properties, being able to meet the requirement of the technology for reinforcing moulding shape of dry transformers. It is an excellent reinforcing material suitable for the production process of dry transformers.

Technical Data:	Unit	Value
Thickness	mm	0.5 +/-10%
Length per roll	m	100
Width	m	0.2 ~ 1.2
Mesh Size (longitude x latitude)	mm	5 x 5
Resin Content	%	25 ~ 35
Tensile Strength	N	800
Breakdown Voltage (Along the surface)	kV	18
Insulation Resistance	Ω	1.0 x 10 <sup>12</sup>
Thermal Class	-	H
Water Absorbtion	%	<3
Colour	-	Natural and Red

Dr. Dietrich Müller GmbH

## Rigidiso<sup>®</sup> RI 40220

---

**Trademark Information:** Rigidiso<sup>®</sup> is a registered trademark of the company Dr. Dietrich Müller GmbH, Germany

---

**Please note:**

The information in this data sheet is based on our current knowledge and experience. They do not disengage the fabricator and user from own tests and inspections because of the plenty of possible effects. There is no judicial binding assurance of certain properties or of the qualification for a concrete application in our declaration. We recommend consulting us in individual cases. The acceptor of our products has to observe possible industrial property rights as well as present laws by himself.

---

Dr. Dietrich Müller GmbH