

Standard products

Cable tie SP 64100

Properties: SP 64100 is a one-sided formed mechanism without metal hooks or elaborate wedge designs. SP 64100 is free of sharp edges or ridges. It is made of high-grade, modified polyimide-granulate and it is self-extinguishing according to UL-94. Due to the high material quality of SP 64100 it offers resistance against brake fluids, greases, power steering fluids, oils, lubricants, hydrocarbons, paint, varnishes and varnish remover. SP 64100 has a temperature resistance of 155°C.

Length (mm)	Width (mm)	Max. bundle-diameter mm	Tensile strength (kgs)
82	2,5	15	8,0
94	2,5	15	8,0
100	2,5	18	8,1
122	2,5	24	8,1
160	2,5	40	8,1
202	2,5	50	8,1
250	2,8	65	14
300	2,8	76	14
143	3,6	33	18,2
150	3,6	33	18,2
202	3,6	50	18,2
251	3,6	66	18,2
303	3,6	76	18,2
371	3,6	102	18,2
121	4,8	24	22,2
160	4,8	38	22,2
179	4,8	41	22,2
192	4,8	43	22,2

Dr. Dietrich Müller GmbH

Cable tie SP 64100

Length (mm)	Width (mm)	Max. bundle-diameter mm	Tensile strength (kgs)
202	4,8	50	22,2
251	4,8	66	22,2
280	4,8	70	22,2
300	4,8	76	22,2
370	4,8	102	22,2
391	4,8	106	22,2
430	4,8	114	22,2
530	4,8	140	22,2

Please note:

The information in this data sheet is based on our current knowledge and experience. They do not disengage the fabricator and user from own tests and inspections because of the plenty of possible effects. There is no judicial binding assurance of certain properties or of the qualification for a concrete application in our declaration. We recommend consulting us in individual cases. The acceptor of our products has to observe possible industrial property rights as well as present laws by himself.