

## tapes

### tesafix® 4965

---

**Material:** tesafix® 4965 is a double-sided polyester-tape with an acrylic adhesive.

---

**Properties:** tesafix® 4965 offers good adhesion on a variety of plastics and has high resistance against softening agents.

---

**Applications:** tesafix® 4965 is used for montage of ABS-parts in automotive, to make rubber or EPDM profiles self-adhesive, rail-bonding in the furniture industry, to close damage on insulating pipes, etc.

---

**Colour:** transparent

---

## tesafix® 4965

Properties	Unit	Value
Base material		PET
Colour		Transparent
Thickness	µm	205
Adhesive		Modified acrylic
Elongation at break	%	50
Tear strength	N/cm	20
Initial adhesion strength to		
steel		11,5
ABS		10,3
Aluminum		9,2
PC		12,6
PE		5,8
PET		9,2
PP		6,8
PS		10,6
PVC		8,7

**Please note:**

The information in this data sheet is based on our current knowledge and experience. They do not disengage the fabricator and the user from own tests and inspections because of the plenty of possible effects. There is no judicial binding assurance of certain properties or of the qualification for a concrete application in our declaration. We recommend consulting us in individual cases. The acceptor of our products has to observe possible industrial property rights as well as present laws by himself.