

tapes

tesafix® 6965

Material: tesafix® 6965 is a double-sided polyester-tape with an acrylic adhesive.

Properties: tesafix® 6965 offers good adhesion on a variety of plastics and has high resistance against softening agents.

Applications: tesafix® 6965 is used for montage of ABS-parts in automotive, crash-pads on car doors, to make rubber and EPDM profiles self-adhesive as well as packing made of corrugated cardboard.

Colour: transparent

tesafix® 6965

property	Unit	Value
Base material		PET
Colour		Transparent
Thickness	µm	205
Adhesive		Modified acrylic
Elongation at break	%	50
Tear strength	N/cm	20
Liner		MOPP
Colour liner		Rot
Thickness liner	µm	80
Weight liner	g/m ²	72
Adhesion strength to steel ABS Aluminum PC PE PET PP PS PVC	N/cm	11,5 10,8 10,2 12,2 5,6 9,8 6,0 10,4 9,6

Please note:

The information in this data sheet is based on our current knowledge and experience. They do not disengage the fabricator and the user from own tests and inspections because of the plenty of possible effects. There is no judicial binding assurance of certain properties or of the qualification for a concrete application in our declaration. We recommend consulting us in individual cases. The acceptor of our products has to observe possible industrial property rights as well as present laws by himself.