

# Gasket material

## Flexseal® FS 30150

**Description:** Flexseal® FS 30150 is a gasket material made of natural rubber.

**Properties:** Flexseal® FS 30150 offers very good elongation and good resistance against strong bases and wear.

**Application:** Flexseal® FS 30150 is used for machine and plant engineering, automotive supply industry and railway vehicles.

**Delivery forms:** Flexseal® FS 30150 can be delivered as customized cut and die-cut part. Dimensions and other delivery forms upon customer request.

properties	Test method	unit	Value
Colour			grey
Specific weight	DIN 53420	g/cm <sup>3</sup>	1,15
Hardness		Shore A	40
Tensile strength		MPa	9
Elongation		%	625
Temperature range		°C	-60 to +230
Oil resistance			Good
Fuel resistance			Good
Acid resistance			Very good
Lye resistance			Very good
Weather resistance			Very good

## Flexseal® FS 30150

---

**Trademark information:** Flexseal® is a registered trademark of company Dr. Dietrich Müller GmbH, Germany.

---

**Please note:**

The information in this data sheet is based on our current knowledge and experience. They do not disengage the fabricator and user from own tests and inspections because of the plenty of possible effects. There is no judicial binding assurance of certain properties or of the qualification for a concrete application in our declaration. We recommend consulting us in individual cases. The acceptor of our products has to observe possible industrial property rights as well as present laws by himself.

---

Dr. Dietrich Müller GmbH