

## Gasket Materials

### Flexseal® EPDM FS 30154 25

**Description:** Flexseal® EPDM FS 30154 25 is a very soft EPDM-quality with excellent resistance against weathering and ozone, as well as a variety of acids and lyes, low-nitrosamine.

**Application:** Flexseal® EPDM FS 30154 25 is used for machine and plant engineering, automotive supply industry and railway vehicles.

**Colour:** black

**Delivery forms:** Flexseal® EPDM FS 30154 25 can be delivered as customized cut or die-cut part. Dimensions and other delivery forms upon customer request.

Property	Unit	Value
Hardness (Shore A)	Shore A	25
Colour	-	Black
Spec. Weight	g/cm <sup>3</sup>	1
Tear strength	MPA	3,5
Elongation	%	450
Temperatureresistance	C°	-30 to +100
Resistance against oil	-	Non-resistant
Resistance against fuel	-	Non-resistant
Resistance against acid	-	Very good
Resistanca against lye	-	Very good
Weather resistance	-	good

Dr. Dietrich Müller GmbH

## Flexseal® EPDM FS 30154 25

---

**Trademark information:** Flexseal® is a registered trademark of company Dr. Dietrich Müller GmbH, Germany.

---

**Please note:**

The information in this data sheet is based on our current knowledge and experience. They do not disengage the fabricator and the user from own tests and inspections because of the plenty of possible effects. There is no judicial binding assurance of certain properties or of the qualification for a concrete application in our declaration. We recommend consulting us in individual cases. The acceptor of our products has to observe possible industrial property rights as well as present laws by himself.

---

Dr. Dietrich Müller GmbH