

## Gaskets

### Flexseal® NR/SBR FS 30166

---

**Description:** Flexseal® NR/SBR FS 30166 is a gasket material made of natural-rubber and styrene-butadiene rubber.

---

**Properties:** Flexseal® NR/SBR FS 30166 offers resistance against strong bases and has limited resistance against acids and wear.

---

**Application:** Flexseal® NR/SBR FS 30166 is used for machine and plant engineering, automotive supply industry and railway vehicles.

---

**Colour:** black

---

**Delivery forms:** Flexseal® NR/SBR FS 30166 can be delivered as customized cut or die-cut part. Dimensions and other delivery forms upon customer request.

---

Dr. Dietrich Müller GmbH

## Flexseal® NR/SBR FS 30166

Properties	Unit	Value
Colour		Black
Spec. weight	g/cm <sup>3</sup>	1,5
Hardness	Shore A	70
Tear strength	MPa	3
Elongation	%	200
Temperature resistance	°C	-20 to +90
Oil resistance		Non-resistant
Fuel resistance		Non-resistant
Acid resistance		Non-resistant
Lye resistance		Limited resistance
Weather resistance		Non-resistant

**Trademarkinformation:** Flexseal® is a registered brand name of the company Dr. Dietrich Müller GmbH, Germany.

**Information:**

All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Dr. D. Müller GmbH makes no warranties as to the accuracy or completeness of the information, and disclaims any liability regarding its use. Dr. D. Müller GmbH only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Dr. D. Müller GmbH be liable for any incidental, indirect or consequential damages arising from the sale, resale, use, or misuse of the product. Dr. D. Müller GmbH Specifications are subject to change without notice. In addition, Dr. D. Müller GmbH reserves the right to make changes in materials or processing without notification to the Buyer, which do not affect compliance with any applicable specification.

Dr. Dietrich Müller GmbH