

mica products

Rigidiso® EPG RI 40515

Application: Rigidiso® EPG RI 40515 is a hard, dense, firm mica sheet and is applied for electrical motors and commutators (collectors). Rigidiso® EPG RI 40515 sheets offer exceptional mechanical and electric properties. Rigidiso® EPG RI 40515 sheets can be manufactured with specific measurements upon customer request.

Components: Rigidiso® EPG RI 40515 is made with a minimum muscovite content of 90% which is impregnated with a specially developed epoxy resin.

Delivery forms: Rigidiso® EPG RI 40515 is available in a thickness of 0,2 – 2,0 mm with dimensions of 1000 mm width and 600/1200 mm length or as stripe or die-cut part. Other delivery forms upon customer request.

Properties	Test method	Unit	Value
Mica content	IEC 60371-2	%	Min. 90
Binder content (Epoxy resin)	IEC 60371-2	%	7-9
Raw density	IEC 60371-2	g/cm ³	2,25-2,4
Compressibility			
Ce-elastic	IEC 60371-2	%	<2,0
Cp-plastic			<2,0
Bending strength	IEC 60371-2	MPa	>300
Flexural modulus	IEC 60371-2	MPa	>70.000
Exudation resistance		°C	300
Breakdown strength		kV/mm	>20
Tracking resistance	IEC 60112	V	>600
Arc resistance	ASTM D 495	s	4

Dr. Dietrich Müller GmbH

Rigidiso® EPG RI 40515

Trademark information: Rigidiso® is a registered trademark of company Dr. Dietrich Müller GmbH, Germany.

Please note:

The information in this data sheet is based on our current knowledge and experience. They do not disengage the fabricator and user from own tests and inspections because of the plenty of possible effects. There is no judicial binding assurance of certain properties or of the qualification for a concrete application in our declaration. We recommend consulting us in individual cases. The acceptor of our products has to observe possible industrial property rights as well as present laws by himself.

Dr. Dietrich Müller GmbH